

Home Search Collections Journals About Contact us My IOPscience

Bismuth electrodes, an alternative in stripping voltammetry

This content has been downloaded from IOPscience. Please scroll down to see the full text. 2013 J. Phys.: Conf. Ser. 466 012025 (http://iopscience.iop.org/1742-6596/466/1/012025) View the table of contents for this issue, or go to the journal homepage for more

Download details:

IP Address: 132.248.12.211 This content was downloaded on 04/04/2014 at 17:36

Please note that terms and conditions apply.

Bismuth electrodes, an alternative in stripping voltammetry

J Barón-Jaimez¹, M R Joya² and J Barba-Ortega²

¹ Grupo Plasnamat, Instituto de Investigaciones en Materiales, Universidad Autónoma de México, DF, México.

² Departamento de Física, Universidad Nacional de Colombia, Bogotá, Colombia.

E-mail: jairob26@hotmail.com

Abstract. The heavy metals are known as highly toxic contaminants, the processes carried out in industry contribute that finally they remain dispersed in effluents and sewage, doing part of the food chain. The importance of controlling the levels of these heavy metals has become an international policy, so it has generated interest in developing new analytical methodologies for its determination [1, 2, 3, 4]. The stripping voltammetry has been considered as a family of electro-sensitive analytical techniques useful for the determination of trace levels of many metals in environmental, clinical and industrial samples [3, 4]. This work presents an overview of these bismuth-based electrodes which were introduced around 2000, which have interesting characteristics for detection of heavy metals and which represent an alternative to mercury electrodes.

1. Introduction

In the last years, the industrialization has come accompanied by different processes, which lead that the heavy metals remain finely dispersed in water, air and soil, as part of the our food chain [1]. Although there are methods with adequate sensitivity for the determination of heavy metals such as atomic absorption, atomic emission spectrometry and ICP-MS, electrochemical methods are one of the most favorable techniques for determination of heavy metal ions because of their low cost and high sensitivity [5]. In analytical chemistry, Anodic Stripping Voltammetry techniques (ASV) are a promising alternative to spectroscopic analysis techniques, particularly by their high sensitivity "ppb" in the detection of the elements trace in fluid and that the sensors are easily coupled to field units in addition of its low cost, low volume of reagents consumed and can be reused for several measures [6]. In this area, the potentiometric sensors represent a very interesting area and with expansion, their great development and acceptance is due to its high sensitivity and the ability to make direct measurements or act as indicators electrodes in valuation, such measures are no affected by the color or turbidity of the sample or analysis solution [7, 8, 9].

2. Results

Although mercury electrodes have been widely used for this type of electrochemical techniques because of its high reproducibility and sensitivity [9], its toxicity makes it less and less popular [3, 9, 10, 11, 12]. Different studies have been assigned to the construction of electrochemical

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution (cc of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1




Figure 1. (Left) Behaviour potential windows for different materials. (Right) Current peaks of Cd, Zn and Pb for voltammetry. a) Bismuth electrode b) Mercury electrode (14).

sensors that do not contain mercury, a variety of different materials have been suggested and explored to produce electrodes of work for this purpose, such as noble metals (Pt, Pd, Au, Aq)and other metals (Ru, Cu, Co, Ni, Pb, Sb, Bi, Al) [7, 13]. However, bismuth is chosen due to its low toxicity [3, 9, 11, 14, 15] wide potential window and ability to form alloys with different metals [9, 10, 16, 17]. This physical-chemical behavior allows its use in the simultaneous detection of multiple electro-active species present in the same sample.

3. Bismuth electrodes in stripping voltammetry

The stripping voltammetry has been considered as a family of electroanalytical techniques more sensitive and useful for determining the level of trace metals in many samples of environmental origin, clinical and industrial, as well as organic components. The risk associated with mercury electrodes is their use, handling and disposal of waste because of its toxicity, this situation generated different researches to overcome these drawbacks; so, around 2000 the electrodes BiFEs (Bismuth Film Electrodes) were introduced, they are fabricated of a bismuth layer deposited on a suitable substrate [3, 4], different materials have been used as electrode substrate such as carbon, glassy carbon, carbon fibers, carbon paste, graphite, graphite impregnated with wax, gold, platinum [10, 16]. These Bismuth electrodes are a promise for replacing the mercury electrodes in stripping voltammetry, as well as their low toxicity, the BiFEs have shown to have electro-analytical properties similar to the mercury electrodes, such as their wide potential window, in addition to its ability to form alloys with various metals, their partial insensitivity to dissolved oxygen, their signals well defined and simple preparation [3]. The current peaks obtained at the voltammograms when uses bismuth electrodes tend to be sharp and well defined [14], in figure (1, right), which enables the identification and quantification of the metals present in the water to reliably way, quickly and economic, could be performed even in the same site where we take the sample. In recent years, different types of modified bismuth and bismuth electrodes have been developed showing a behavior comparable to MFEs (Mercury Film Electrodes) in ASV, reported methods for preparing electrodes with an active surface of bismuth have been fabricated by modifying of volume the surface of the solid electrode with metallic bismuth such as mixtures of powders of bismuth, bismuth oxide and carbon [14, 18], thermal evaporation [19], sputtering [4, 11] and electro-deposits compound Bi (III) both ex situ [10, 12, 20, 21] as in situ [9, 10, 17, 15, 21, 22, 23, 24, 25] in a conductive material. The




Figure 2. Square-wave stripping voltammograms for increasing concentration of copper, lead, cadmium and copper (21).

method most widely used for the preparation of BiFEs is electrochemical performed by static potentiometry (in situ or ex situ) and occasionally, by galvanostatic method, cyclic potential or pulse amperometry. However deposits by electrochemical means involving the use of salts of Bi (III), which can complicate experimental procedures and requires a conductive substrate [3, 4]. There are several reports in the literature of bismuth based electrodes were tested for the determination of trace metal ions and occasionally for the detection of organic compounds using voltammetric techniques in various forms. Some of the metals that have been reported so far include Cd, Pb, Zn, Tl, In, CuNi, Co, Fe, Al, Mo, V, Ti, U and Cr [10, 26]. Furthermore, metals have been detected in trace amounts in a variety of biological samples (hair, urine and blood) [10, 26] and environmental samples (air, tap water, sea water, river water, drains and water soils) [7, 14, 16], foodstuffs (tea, cabbage, celery, spinach, wine and tomato sauce) [7, 10, 14, 15] and Petrol [7].

4. Conclusions

In the last decade, bismuth electrodes manufactured by different methods and due to their physico-chemical Characteristics are a promise for stripping voltammetry in the determination of heavy metals especially, these electrodes are bringing us more and more to the determination of a single digit ppb of these elements, which in most cases are the limits permitted by international health organization for human consumption.

Acknowledgements

The authors would like to thank Sandra E. Rodil of the Plasnamat and Ely Dannier V-Niño of LNDC-UFRJ by very useful discussions.

References

- [1] www.auroville.org. Auroville innovative Urban Management IND-015 1 annexes
- [2] Foro Interguvernamental de Seguridad Química IFCS 2006 Budapest
- [3] C Kokkinos, I Raptis, A Economou and T Speliotis 2009 Procedia Chemistry 1 1039
- [4] C Kokinos and A Economous 2008 *Electrochimica Acta* 53 294
- [5] O Hernandez 2006 Furoiltioureas: Naturaleza de sus Complejos con CdCl₂ y HgCl₂ y su Utilización en Sensores Electroquímicos (España: Universidad de Cadiz)
- [6] I Sierra 2009 http://www.madrimasd.org/informacionidi/noticias/noticia.aspid=38007
- [7] F Arduini and J Quintana 2010 Trends in Analytical Chemistry 2-11 1295
- [8] M J Gismera 2006 Desarrollo de Nuevos Sensores Potenciometricos para Metales Basados en Receptores con Grupos Tio y Ditio (Madrid: Universidad Autónoma de Madrid)
- [9] L Cao and J Jia 2008 Electrochimica Acta 53 2177
- [10] A Economou 2005 Trends in Analytical Chemistry 24-4 334
- [11] C Kokkinos, A Economou 2007 Electrochemistry Communications 9 2795
- [12] E Hutton, B Ogoreve, S Hocevar, F Weldon, M R Smyth and J Wang 2001 Electrochemistry Communications 3 707
- [13] R Pauliukaite, S Hocevar, B Ogorevc and J Wang 2004 Electroanalysis 16 719
- [14] J Wang 2005 Electroanalysis **17** 1341
- [15] H Xu, L Zeng 2008 Food Chemistry 109 834
- [16] S Hocevar S, I Svancara, K Vytras and I Svancara 2005 Electrochemica Acta 51 706
- [17] L Baldrianova, I Svancara, M Vicek, A Economou and S Sotiropoulos 2006 Electrochimica Acta 52 481
- [18] L Kumari, S Lin, J Lin, Y Ma, P Lee and Y Liou 2007 Applied Surface Science 253 5931
- [19] N Serrano, A Alberich, J M Diaz-Cruz, C Arino and M Esteban 2008 Electrochemica Acta 53 6616
- [20] I Svancara, L Baldrianova, M Vicek, R Metelka and K Vytras 2005 Electroanalysis 17 120
- [21] J Wang, J Lu, U Kirgoz, S B Hocevar and B Ogorevc 2001 Analytical Chimica Acta 434 29
- [22] C Prior, C E Lenehan and G S Walker 2007 Analytical Chimica Acta 598 65
- [23] C H Xiong, H Q Luo and N B Li 2011 Journal of Electroanalytical Chemistry 651 19
- [24] Y Wu, N B Li and H Q Luo 2008 Sensor and Actuator B: Chemical 133 677
- [25] Z Zou, A Jang, P Wu, J Do, J Han, P Bishop and C Ahn 2007 Eleventh International Conference on Miniaturized Systems for Chemistry and Life Sciences 251
- [26] R Cornelis 2003 Handbook of Elemental Speciation: Techniques and Methodology (England: Wiley)